

## **Technical Data Sheet**

## Renovare™ Renew and Refresh





### **Product Description**

Renovare<sup>™</sup>, part of the AntiBlu<sup>®</sup> product line from Arxada, is designed to Refresh and Renew wood pallets, making them clean and bright for reuse within the industry. Renovare<sup>™</sup> is an organic-based blend of food grade chemicals for industrial and commercial use.

#### **Product Use**

Factory applied and available through River City Wood, Renovare™ is an organic-based blend of food grade chemicals for industrial and commercial use.

#### **Product Storage**

Store away from other materials in a corrosive resistant container with a resistant inner liner. Protect from sunlight. It is recommended to store Renovare™ at temperatures where the bulk liquid will not exceed 86°F / 30°C. Keep cool. Store locked up.

### **Product Disposal**

Dispose of contents and containers at an approved waste disposal plant according to state and local regulations. Do not contaminate water, food, or feed by storage and/or disposal.

### **Product Comparison Test**



Renovare™ diluted 1:1

No treatment

5% bleach



### **Container Disposal**

Empty residue from containers, rinse container well.

### Safety Recommendations

Read product label before using.

Wear protective gloves, protective clothing, eye protection, and face protection. Work in a well-ventilated environment. Wash hands thoroughly after handling.

Keep away from heat, sparks, open flames, and hot surfaces. Keep and store away from clothing and combustible materials.

Do not eat, drink or smoke when using this product.

#### **Product Contents**

Product contains Peroxyacetic acid, Acetic Acid, and Hydrogen Peroxide.

#### **Directions for Use**

#### Read product label before using.

Renovare<sup>™</sup> may be applied to wood and wood products by spray methods. It may also be applied in a backpack or tank sprayer as a dilute solution when mixed with water in a contained and well-ventilated area. Dilutions can be adjusted based on the severity of mold and mildew staining, and weathering. Brushing or scrubbing may be required for exceptionally weathered or stained material.

For spray applications:

Mix one gallon of Renovare to 1-50 gallons of water.

#### **Available Sizes**

- 5 Gallon jug
- 15 Gallon drum
- 30 Gallon drum

#### **Physical Characteristics**

Property	Values
Physical state	Liquid
Color	Colorless
рН	< 1 (1:10)
Flash point	> 207° F / > 98 ° C
Viscosity	10-20 cSt at 20°C / 68°F
Specific Gravity	1.145 g/mL
Water solubility	Complete

#### **Frequently Asked Questions**

# 1. What products are included in the AntiBlu® product line?

In addition to AntiBlu® sapstain control products, the AntiBlu® line includes defoamers, brighteners, and end sealers. This line also includes our Mycostat® products. See wolmanizedwood.com for more information on these products.

# 2. Does this product work for hardwoods and softwoods?

Yes. Use levels will vary depending on application and severity of weathering, mold/mildew/algae staining, and general staining. Renovare<sup>™</sup> can be used on hardwoods and softwoods, in a spray treatment method. It is specially designed to revitalize pallets so they can be reused within the industry.

# 3. Can this product rehabilitate the appearance of wood?

For wood products whose appearance has been affected by mold, application of Renovare™ will help clean the wood and maintain the appearance for some time.

#### 4. Why should I have confidence in these products?

Renovare<sup>™</sup> is from the manufacturers of the Antiblu<sup>®</sup> line of products, which as a history of trusted performance. It has been tested for effectiveness.

# 5. Who should I contact if I have a problem with worker exposure or spills?

Call: CHEMTREC 1-800-424-9300 [CCN 864796].

#### 6. Who should I contact for additional information?

Contact Kevin McLaughlin at River City Wood - kmm@rivercitywood.com or send a message to wolmanizedwoodinfo@arxada.com.

# arxada

1200 Bluegrass Lakes Parkway Alpharetta, GA 30004 470-504-1301 wolmanizedwood.com Use wood preservatives safely. Always read the label and product information before use. All product information corresponds to Arxada's knowledge on the subject at the date of publication, but Arxada makes no warranty as to its accuracy or completeness and Arxada assumes no obligation to update it. Product information is intended for use by recipients experienced and knowledgeable in the field, who are capable of and responsible for independently determining the suitability of ingredients for intended uses and to ensure their compliance with applicable law. Proper use of this information is the sole responsibility of the recipient. This information relates solely to the product as an industrially

applied, high pressure wood preservative. It may not be applicable, complete or suitable for the recipient's finished product or application; therefore republication of such information or related statements is prohibited. Information provided by Arxada is not intended and should not be construed as a license to operate under or a recommendation to infringe any patent or other intellectual property right. No claims are made herein for any specific intermediate or end-use application. All trademarks belong to Arxada or its affiliates or to their respective third parties and are used here only for informational purposes.